



## 240V WIRED RADIO FREQUENCY (RF) INTERCONNECTION 1YR & 10YR REPLACEABLE BATTERY MODEL OPTIONS

The Emerald Planet Photoelectric RF Smoke Alarm is powered by 240V mains power and supported by either a 1-year 9V or 10-year lithium replaceable battery back-up.

The alarm is fitted with a test/hush/silence button to facilitate testing of the alarm.

The silence function also allows the alarm and alarm system to be silenced in the case of a false alarm.

The RF capability enables connection with up to 40 alarms on one wireless network, with installation and maintenance made easy using the RF easy-fit base.

### FEATURES

- Slimline base plate and RF easy-fit base included
- RF enabling connection with up to 40 alarms
- High visibility LED indicator lights for test/hush/silence and fault warnings
- Loud alarm: 85dB(A) @ 3m
- CSIRO ActivFire listed
- Meets Australian smoke alarm standards (AS3786:2014)
- 5 year warranty



### SPECIFICATIONS

<b>MODEL NUMBER</b>	EP-HW-240-Li10 EP-HW-240-R1
<b>NORMAL OPERATING &amp; STORAGE TEMPERATURE</b>	0° to 40°
<b>DIMENSIONS</b>	125mm dia. 40mm deep
<b>WEIGHT</b>	190g
<b>WARRANTY</b>	5 Years

<b>POWER</b>	240V with 1yr 9V or 10yr lithium replaceable battery back-up
<b>SENSOR</b>	Photoelectric optical chamber
<b>ALARM VOLUME</b>	>85dB(A) @ 3m
<b>INTERCONNECT</b>	Radio Frequency (RF) enabling connection with up to 40 alarms on one wireless network
<b>RF COMPATIBILITY</b>	Compatible with EP-RF-Li10 smoke alarms
<b>NORMAL OPERATING &amp; STORAGE HUMIDITY</b>	15% to 95% relative humidity (non-condensing)