



## 10YR BATTERY POWERED RADIO FREQUENCY (RF) INTERCONNECTION

The Emerald Planet (EP-RF-Li10) Photoelectric Smoke Alarm is powered by a non-replaceable 10-year rated Lithium battery.

The alarm is fitted with a test/hush/silence button to facilitate testing of the alarm.

The silence function allows the alarm system to be silenced in the case of a false alarm. Silencing one alarm will silence all connected alarms.

This alarm can be used as a stand-alone alarm or can be connected with up to 40 alarms. This allows all smoke alarms connected to activate simultaneously.

## FEATURES

- 10 year 3V Lithium ion battery
- RF interconnectable with up to 40 alarms on one wireless network
- High visibility LED indicator lights for test/hush/silence and fault warnings
- Loud alarm – 85dB(A) @ 3m
- CSIRO ActivFire listed
- Meets Australian smoke alarm standards (AS3786:2014)
- 5 year warranty



## SPECIFICATIONS

<b>MODEL NUMBER</b>	EP-RF-Li10	<b>POWER</b>	DC 3V 10yr rated Lithium ion battery (non-removable)
<b>NORMAL OPERATING &amp; STORAGE TEMPERATURE</b>	0° to 40°	<b>SENSOR</b>	Photoelectric optical chamber
<b>DIMENSIONS</b>	112mm dia. 38mm deep	<b>ALARM VOLUME</b>	>85dB(A) @ 3m
<b>WEIGHT</b>	190g	<b>INTERCONNECT</b>	Wireless RF interconnection. Up to 40 units per network
<b>WARRANTY</b>	5 Years	<b>NORMAL OPERATING &amp; STORAGE HUMIDITY</b>	15% to 95% relative humidity (non-condensing)
		<b>INCLUDES</b>	Screws and mounting plate
		<b>COMPATIBILITY</b>	RF smoke alarm is compatible with - <ul style="list-style-type: none"> <li>• 240V smoke alarms with RF base</li> <li>• Self-compatible (i.e. additional units of the same model)</li> </ul>