



## UNI SERIES EMERGENCY BATTEN

The Uni Emergency Batten with a premium, 3 hour backup Lithium Nanophosphate (LiFePO4) battery, is fully compliant to the AS2293 emergency lighting standard.

With switchable tri-colour settings and built-in adjustable motion sensors, the Uni Emergency Batten allows customisation to a range of preferences. The Uni Emergency Batten also includes a self-test function to ensure that the battery is fully operational. Automated tests are performed at varying intervals with a visual warning light displayed when a problem is detected.

## FEATURES

- Maintain emergency light
- 4.5W/3hr emergency power
- CO:D63, C90:D50
- Sensor with adjustable dim levels and hold times
- Self-test functionality
- IP20/65 and IK08/10 rating model options

## SPECIFICATIONS

POWER FACTOR	>0.9
CRI	>80
BEAM ANGLE	120°
IP RATING	20 or 65
LIFETIME (L70)	>60,000hrs
WARRANTY	5 Years

DETECTION RANGE	5 or <b>10</b> metres
HOLD TIME	1m, <b>5m</b> , 15mins or infinite
DAYLIGHT SENSOR	<b>50Lux</b> or disabled
STANDBY PERIOD	0s, 5m, 30m or <b>infinite</b>
STANDBY LEVEL	<b>10</b> , 20, 30 or 50%

Highlighted values = sensor default settings

MODEL NUMBER	CCT	DIMENSIONS	WATT	LCP	LPM	LUMENS	EFFICACY
<b>IP20 TRI-COLOUR EMERGENCY WITH SENSOR</b>							
EP-UNI-TES620-18	4/5/6000K	600mm	18	18.31	1.8	2283	125lm/W
EP-UNI-TES1220-15	4/5/6000K	1200mm	15	15	1.5	2000	133lm/W
EP-UNI-TES1220-25	4/5/6000K	1200mm	25	24.71	2.5	3307	134lm/W
EP-UNI-TES1220-35	4/5/6000K	1200mm	35	35	3.5	4200	120lm/W
<b>IP65 TRI-COLOUR EMERGENCY WITH SENSOR</b>							
EP-UNI-TES665-18	4/5/6000K	600mm	18	18	1.8	2200	125lm/W
EP-UNI-TES1265-25	4/5/6000K	1200mm	25	24.88	2.5	2957	119lm/W
EP-UNI-TES1265-35	4/5/6000K	1200mm	35	34.94	3.5	4351	125lm/W