



FEATURES

- Built-in high efficiency SMD chips
- Metal steel base
- Highly transparent opal polycarbonate diffuser
- Large 6mm terminal block for easy installation
- Quick install modular design
- High efficiency 120Lm/W

INCLUDES

- Mounting accessories

INSTALLATION OPTIONS

- Surface mounted
- Suspended(suspension kit is required)

APPLICATIONS

- Offices
- Car parks and garages
- Stations
- Industrial
- Commercial

WARRANTY

- Three years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)
	IP20	Non dim	Ra≥80		

Part No.	Order Code	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Size(L*W*H)mm	Net Weight (kg)
213554	213554	220-240V	18W	0.9	4000K	2160lm	120°	35000h	1200*80*65	1.92
213555	213555	220-240V	25W	0.9	4000K	3000lm	120°	35000h	1200*80*65	1.92

Part No.	Model No.	HEERS Status	VEET Status	IPART Status
213554	YKT8BG2-L120 18W	Pending	Pending	Pending
213555	YKT8BG2-L120 25W	Pending	Pending	Pending

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+45 °C

